



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/828,067	04/06/2001	Don E. Curry	005040/TCG/PMD/LE	7268

32588 7590 10/03/2005

APPLIED MATERIALS, INC.
2881 SCOTT BLVD. M/S 2061
SANTA CLARA, CA 95050

EXAMINER

ZERVIGON, RUDY

ART UNIT	PAPER NUMBER
----------	--------------

1763

DATE MAILED: 10/03/2005

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No. 09/828,067	Applicant(s) CURRY ET AL.	
	Examiner Rudy Zervigon	Art Unit 1763	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 29 September 2005.
- 2a) ☐ This action is FINAL. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 21-35 and 38-41 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 21-35 and 38-41 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|--|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input checked="" type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. <u>20050929</u> . |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. Applicant's arguments, see interview summary of September 29, 2005, with respect to the rejections of all claims under 35 USC 103 have been fully considered and are persuasive. Therefore, the rejection has been withdrawn. However, upon further consideration, new grounds of rejection is made in view of Sivaramakrishnam; Visweswaren et al. (US 5,531,183 A).

Claim Rejections - 35 USC § 103

2. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.

3. Claims 29, 30, 31, 33, and 34 are rejected under 35 U.S.C. 103(a) as being unpatentable over Itsudo et al (JP05-198512) in view of Sivaramakrishnam; Visweswaren et al. (US 5,531,183 A). Itsudo teaches:

- i. A wafer (2; Figure 6) processing apparatus (Figure 6, 8; abstract), comprising: a processing chamber (1; Figure 6; abstract) defined by a lower wall, an upper wall (8; Figure 6) and side walls extending from the lower wall to the upper wall (8; Figure 6), a wafer (2; Figure 6) supply opening (not shown; inherent) being formed in one of the walls for transferring a wafer (2; Figure 6) into the chamber (1; Figure 6; abstract); a susceptor (6; Figure 1) in the chamber (1; Figure 6; abstract) on which the wafer (2; Figure 6) can be located so that an upper surface of the wafer (2; Figure 6) faces the upper wall (8; Figure 6); a manifold (9; Figure 6) component located on the chamber (1; Figure 6; abstract) and, together with the upper surface of the upper wall (8; Figure 6), defining a manifold cavity (9; Figure 6); an exhaust line (4; Figure 6) connected to the chamber (1; Figure 6; abstract), for flowing a gas from the chamber (1; Figure 6;

Art Unit: 1763

abstract), connected such that the gas has a tendency to flow toward the exhaust line (4; Figure 6); and a gas supply line (12; Figure 6) connected to the manifold (9; Figure 6) component, wherein the upper wall (8; Figure 6) has a plurality of gas supply openings (10; Figure 6, 8), each of the gas supply openings (10; Figure 6, 8) formed into an upper surface and out of a lower surface of the upper wall (8; Figure 6) such that each gas supply opening is defined by a corresponding interior surface of the upper wall (8; Figure 6), the gas supply openings (10; Figure 6, 8) being nonuniformly (Figure 8) distributed over the upper wall (8; Figure 6) to create a flow pattern that counteracts the tendency of the gas to flow toward the exhaust line (4; Figure 6), and thus promotes even processing over the upper surface of the wafer (2; Figure 6), as claimed by claim 29 – When the structure recited in the reference is substantially identical to that of the claims, claimed properties or functions are presumed to be inherent (In re Best, 562 F.2d 1252, 1255, 195 USPQ 430, 433 (CCPA 1977); MPEP 2112.01).

- ii. The apparatus (Figure 6, 8; abstract) of claim 29 wherein the openings (10; Figure 6, 8) are more densely located on one side of the upper wall (8; Figure 6) than on another side thereof, as claimed by claim 30
- iii. The apparatus (Figure 6, 8; abstract) of claim 30 wherein the openings (10; Figure 6, 8) are substantially equal in size, as claimed by claim 31
- iv. The apparatus (Figure 6, 8; abstract) of claim 29 wherein the exhaust line (4; Figure 6) is connected at an exhaust location which is off-center with respect to a center point (geometric center of 8; Figure 8) of the wafer (2; Figure 6), when viewed from above, so that the gas exits out of the chamber (1; Figure 6; abstract) at the exhaust location which

Art Unit: 1763

is off-center with respect to a center point (geometric center of 8; Figure 8) of the wafer (2; Figure 6), as claimed by claim 33

- v. The apparatus (Figure 6, 8; abstract) of claim 33 wherein a channel (present, not labelled; Figure 1) is defined within the chamber (1; Figure 6; abstract), the channel (present, not labelled; Figure 1) being concentric with the wafer (2; Figure 6), gas flowing radially outwardly over the wafer (2; Figure 6) into the channel (present, not labelled; Figure 1), from the channel (present, not labelled; Figure 1), to the exhaust location into the exhaust line (4; Figure 6), as claimed by claim 34 – When the structure recited in the reference is substantially identical to that of the claims, claimed properties or functions are presumed to be inherent (In re Best, 562 F.2d 1252, 1255, 195 USPQ 430, 433 (CCPA 1977); MPEP 2112.01).

Itsudo does not teach a gas supply connected via a gas supply line opening formed through an upper surface of the manifold cavity.

Sivaramakrishnam teaches a gas supply (40,60,80; Figure 2) connected via a gas supply line opening formed through an upper surface (top of 10) of a manifold cavity (38).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to add Sivaramakrishnam's gas supplies and for Itsudo to optimize the relative location of his gas supply line opening.

Motivation to add Sivaramakrishnam's gas supplies and for Itsudo to optimize the relative location of his gas supply line opening is to use process gas sources as precursors for operations and to optimize desired process gas flows as taught by Itsudo (abstract). It is well established that the rearrangement of parts is considered obvious to those of ordinary skill (In re Japikse , 181

Art Unit: 1763

F.2d 1019, 86 USPQ 70 (CCPA 1950); In re Kuhle , 526 F.2d 553, 188 USPQ 7 (CCPA 1975); Ex parte Chicago Rawhide Manufacturing Co. , 223 USPQ 351, 353 (Bd. Pat. App. & Inter. 1984).; MPEP 2144.04)

4. Claims 32, 35, 38, 39, and 40 are rejected under 35 U.S.C. 103(a) as being unpatentable over Itsudo et al (JP05-198512) and Sivaramakrishnam; Visweswaren et al. (US 5,531,183 A) in view of Nguyen, Tue (US 6,444,039 B1). Itsudo and Sivaramakrishnam are discussed above. Itsudo further teaches Itsudo's apparatus (Figure 6, 8; abstract) of claim 29 wherein Itsudo's exhaust line (4; Figure 6) is connected at an exhaust location which is off-center with respect to a center point of Itsudo's wafer (2; Figure 6), when viewed from above, so that Itsudo's gas exits out of Itsudo's wafer (2; Figure 6) at Itsudo's exhaust location which is off-center with respect to a center point of Itsudo's wafer (2; Figure 6), as claimed by claim 40. Itsudo further teaches Itsudo's apparatus (Figure 6, 8; abstract) of claim 40 wherein Itsudo's openings (10; Figure 6, 8) are formed to increase a flow rate of Itsudo's gas over Itsudo's wafer (2; Figure 6) farther from Itsudo's exhaust location, as claimed by claim 41 – When the structure recited in the reference is substantially identical to that of the claims, claimed properties or functions are presumed to be inherent (In re Best, 562 F.2d 1252, 1255, 195 USPQ 430, 433 (CCPA 1977); MPEP 2112.01).

Itsudo and Sivaramakrishnam do not teach:

Art Unit: 1763

- i. Itsudo's apparatus (Figure 6, 8; abstract) of claim 29 wherein flow of gas in Itsudo's chamber (1; Figure 6; abstract) is laminar, as claimed by claim 32
- ii. Itsudo's apparatus (Figure 6, 8; abstract) of claim 34 wherein Itsudo's openings (10; Figure 6, 8) are more densely located farther from Itsudo's exhaust location, as claimed by claim 35
- iii. Itsudo's apparatus (Figure 6, 8; abstract) of claim 29 wherein there are first and second ones of Itsudo's openings (10; Figure 6, 8) on opposing sides of a point (geometric center of 8; Figure 8) on Itsudo's upper wall (8; Figure 6), Itsudo's first opening having a lower end which is angularly displaced relative to an upper end thereof in a selected direction about Itsudo's point (geometric center of 8; Figure 8), and Itsudo's second opening having a lower end which is angularly displaced relative to an upper end thereof in Itsudo's selected direction, so that Itsudo's openings (10; Figure 6, 8) jointly create a circular gas flow pattern in Itsudo's chamber (1; Figure 6; abstract), as claimed by claim 38 – Applicant's Figure 4, 5 embodiment
- iv. Itsudo's apparatus (Figure 6, 8; abstract) of claim 38 wherein a third of Itsudo's openings (10; Figure 6, 8), on a side of Itsudo's second opening opposing Itsudo's first opening, has a lower end which is displaced in Itsudo's first direction relative to an upper end thereof, as claimed by claim 39

Nguyen teaches a portion (vertical part) of a gas distribution plate (111; Figure 10) including injection holes (117, Figure 10) with Applicant's claimed angular displacement as per Applicant's Figures 4, 5.


Art Unit: 1763

It would have been obvious to one of ordinary skill in the art at the time the invention was made to angle Itsudo's gas supply openings (10; Figure 6, 8) as taught by Nguyen, further to process the wafer under laminar flow including optimized hole distributions as taught by Itsudo.

Motivation to angle Itsudo's gas supply openings (10; Figure 6, 8) as taught by Nguyen, further to process the wafer under laminar flow including optimized hole distributions as taught by Itsudo is for influencing flow patterns of Itsudo's process gases to achieve controlled CVD film thickness distributions as taught by Itsudo (abstract).

Conclusion

5. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Examiner Rudy Zervigon whose telephone number is (571) 272.1442. The examiner can normally be reached on a Monday through Thursday schedule from 8am through 7pm. The official fax phone number for the 1763 art unit is (703) 872-9306. Any Inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Chemical and Materials Engineering art unit receptionist at (571) 272-1700. If the examiner can not be reached please contact the examiner's supervisor, Parviz Hassanzadeh, at (571) 272-1435.

Handwritten signature of Rudy Zervigon, dated 4/20/15.